



**Specifications Ledvance LED  
Floodlight MAX Wall Grey 600W  
82000lm 50Dx110D - 757 Daylight |  
IP66 - Asymetrical**

[View Product](#)

## General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 243785                                  |
| EAN                      | 4058075580619                           |
| Manufacturer Code        | 4058075580619                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | FL MAX LUM P 600W 757 ASYM50X110WALLEDV |
| Any Lamp all-in warranty | 3 Years                                 |
| Average Lifetime (h)     | 100000                                  |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 600W            |
| Replaces (Watt)             | 1000            |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 757 Cool White  |
| Colour temperature (Kelvin) | 5700 Cool White |
| Colour Rendering (Ra)       | 70-79           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 82000lm         |
| Lumen per watt              | 137             |

|                       |                |
|-----------------------|----------------|
| Beam Angle (degree)   | 50x110         |
| Power factor          | >0.90          |
| Product Type Category | LED Floodlight |

## Fixture Information

|                        |                             |
|------------------------|-----------------------------|
| Mounting Method        | Surface                     |
| Including bulb         | Yes                         |
| Fixture Connection     | Terminal, 3-Pole (L, N, PE) |
| Optical Cover          | Glass                       |
| Light Distribution     | Asymmetrical                |
| IP-Rating              | IP66                        |
| Impact Protection (IK) | IK08 - 5 joules             |
| Operating Temperature  | -30 to +50                  |
| Colour of the Fixture  | Aluminium, White            |
| Housing                | Aluminium                   |
| Colour of material     | White/Aluminium             |
| Series                 | Max                         |

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1300 |
| Width (mm)  | 591  |
| Height (mm) | 279  |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation

Type of sensor
 

 No Sensor


 Up to **7 years warranty**


**Easy** return process